

Amplifiers



9934



9935

Power supply



9933

Amplifiers

Reference	9934	9935
inputs	4 SAT	4 SAT + 1 Terr
Outputs	4	5
Frequency range	950-2300 MHz	Sat.: 950-2300 MHz Terr.: 5-65 MHz + 87-862 MHz
Gain	20-25 dB (sloped)	Sat.: 20-25 dB (sloped) Terr.: 87-862 MHz - 20-27 dB (sloped) return path: - 1 dB
Noise figure	5 dB	Sat.: 5 dB - Terr.: 6 dB
Gain adjustment	20 dB	Sat.: 20 dB - Terr.: 20 dB
Max. output level	110 dB μ V (-35 dB/IM3)	Sat.: 110 dB μ V (-35 dB/IM3) Terr.: RP: passive 87-862 MHz: 114 dB μ V (-54 dB/IM3)
Consumption	400 mA from 15 VDC external power supply or input / output	500 mA from 15 VDC external power supply or input / output
Dimensions	158 x 102 x 51 mm	158 x 102 x 51 mm

Power supply

Reference	9933 / 9933 UK
AC input	230 V~/50 Hz
DC output	15 VDC
Max. output current	2.0 Amp
Connector	Jack 2,1 mm / female
Dimensions	176x71x47 mm