



2-In-1 Rework System

Soldering and Rework, Excellent efficiency

QUICK / 707Series



QUICK 707D+



QUICK 708D+



QUICK 709D+




WeChat official account

www.quick-global.com

▼ Features

- Large power, rapid heating, abundant thermal capacity, high heating efficiency.
- LCD display, dynamic visual display of temperature of soldering and rework, digital temperature calibration.
- 2-In-1 design, multi-usage and save space.
- Brushless vortex airflow fan, stepless adjustment, soft airflow.
- All metal design for heater, durable, low voltage heating, safety, separate design of heater and soldering tip, low cost of consumables.
- Intelligent auto sleeping, energy saving, expand the lifetime of heating element etc.
- All metal design for iron stand with copper brass, no harm to soldering tip.
- The handle is more ergonomic, light and comfortable.

▼ Standard accessories



▼ Specifications

Model	707D+	708D+	709D+
Power	800W (Soldering station 70W)	700W (Soldering station 70W)	1350W(Soldering station 70W)
Display type	LCD		
Operating voltage	220V AC		
Temperature range(Soldering)	100~480°C		
Temperature range(Hot air)	100~500°C		
Temperature stability(Hot air)	±5°C (Stationary air, no load)		
Temperature stability(Soldering)	±2°C (Stationary air, no load)		
Airflow	30L/min (Max)	40L/min (Max)	50L/min (Max)
Range of air volume	10~100 Class	1~100 Class	
Ambient temperature	0~40°C		
Tip to ground potential	<2mV		
Tip to ground resistance	<2Ω		
Outer dimensions	98*170*151mm	180*210*131mm	
Weight	About 2.6 Kg	About 3.3 Kg	