THANK YOU FOR PURCHASING A GALLUNOPTIMAL SOLDERING IRON. Please read the operating instructions before use and keep them in a safe place easily accessible to all users.

The soldering iron needs to be tested before it leaves the factory, so the soldering tip may cover a small amount of tin, and the casing will be slightly yellowing, which is a normal phenomenon.

## 

Disregarding the following instructions can lead to serious injury or death of the user. When the unit is switched on, the soldering tip automatically heats up to the last set temperature. There is a risk of burns on the surfaces!

The device is designed for soldering soft solder with different temperatures. Any other use is not permitted. Do not touch the metal parts on the tools during operation and immediately after switching off, CAUTION! Danger of burns!

Do not use the device near flammable materials and components.

Use a heat-resistant work surface and keep your workplace clean.

Solders, fluxes and heated materials can develop harmful properties and should be extracted in a controlled manner. Do not inhale these toxic vapours or gases and ensure adequate ventilation.

The device may only be used for operation in dry indoor areas. Protect the device from liquids and moisture, even by possibly wet hands. Otherwise, short circuits and electric shocks could be caused.

Inform other people in the work area that the temperature can be very high during operation. Switch off the unit as soon as the work is finished to avoid danger.

Do not leave the appliance unattended while it is switched on.

After switching off, wait until the heated parts have reached room temperature if you want to touch parts or change parts.

Specification	Valtage	Power	Temp. range	Stability	Heater	Heating indication	Temp. unit	Display
-	110/240VAC	150W	80-480°C	+/-2°C	PTC	LED	°C/°F	LCD

<b>Turn it on:</b> Plug the power cable into the socket and press Power at the soldering iron.	Stainless ste outer casing	Minus button Power/M	enü button
With the +/- keys 9 different temperature setting ranges can be selected.	325 3	Shell Add Baccol Display	power cabel P°C/617°F, P°C/752°F,

press Menü ⇒ long ⇒ change Temperatur ⇒ short ⇒ Temperature compensation ⇒ short ⇒ Temperature unit ⇒ short ⇒ Standby ⇒ short ⇒ Working mode

Menu		
Change Temperatur 332 3	press +/- short 1°K, long fast change	
Temperature compensation 20 d	press +/- short 1°K, long fast change (max.+/-50°C/90°F	
Temperature unit	press +/- short, °C or °F	
Standby SLP 0	press +/- short, 1=on, 0=off	

When the Soldering iron is heated, the power light flashes, the brightness changes according to the power level and the selected gear light is long.

	Error messages			
	K-E	H-E and the soldering iron does not heat means the heating element is defective.		
ſ	S-E	S-E means the sensor or the control unit is defective.		

## Soldering tips



## EU declaration of conformity according to Low-Voltage Directive 2014/35/EC (Nr. 01-20)

The manufacturer/ distributor

Bräunlich GmbH Am Heideberg 26 06886 Lutherstadt Wittenberg

hereby declares that the following product

Product designation:	GALLUNOPTIMAL Soldering iron
Trade name: Trade	GALLUNOPTIMAL Sprint150
Model name:	GOSprint150

fulfills to the provisions of the Low-Voltage Directive 2014/35/EC - including the changes which applied at the time of the declaration.

The following harmonised standards have been applied: "DIRECTIVE OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the harmonisation of the laws of the Member States relating to electromagnetic compatibility".

The following national or international standards (or parts/clauses of them) and specifications were applied:

EN 60335-2-45:202 + A1:2008 + A2:2012 EN 60335-1:2012 + A11:2014 + A13:2017 EN 62233:2008

Place: Lutherstadt Wittenberg Date: 20.4.2020

(Signature) Mr. Tobias Bräunlich, CEO

Tel. +49 (0) 3491/6181-0 e-mail: info@loet-shop www.loet-shop.de Bräunlich GmbH Am Heideberg 26 D-06886 Lutherstadt Wittenberg